Accessories Fittings

PVC Coated STG Rigid Conduit Knockout Hub with Ground 3/4 Inch

c UL us LISTED

Catalog Number	RESTPRSTG2
UPC	785928565991

DESCRIPTION

3/4 Inch PVC Coated STG Rigid Conduit Knockout Hub with Ground are used for connections using rigid PVC coated conduit.



APPLICATION

- Used with Rigid and IMC conduit to terminate of electrical circuits through wall of an enclosure
- For use indoors or outdoors with rigid conduit and IMC
- Ideal for pharmaceutical; chemical and food processing; pulp/paper; nuclear; solar and commercial construction applications

FEATURES

- Tapered female threads for rigid/IMC conduit; NPSM male threads
- Easy installation and smooth pulling service for labor savings
- Multiple certifications provide users peace of mind

General Information

Color	Gray
Material	PVC Coated Rigid
Country of Origin	USA

DIMENSIONS

Dimension A (Inches)	1.47
Dimension B (Inches)	2.25
Dimension C (Inches)	0.91
Max Wall Thickness	0.19
Nominal Weight (lbs)	0.3
Weight (lbs)	0.32

STANDARDS

NEC/CEC	Class II, Division 1 & 2
NEC/CEC	Class I, Division 2
NEC/CEC	Class III, Division 1 & 2
UL 514B	UL Listed File #E200413