Enclosures New Sentry Series


PVC Enclosure 6 x 6 x 4 Inches New Sentry Series with Opaque Lift Off Cover


c UL us LISTED

Catalog Number	J664PVC
UPC	785928500503

DESCRIPTION

6H x 6W x 4D Inches New Sentry Series PVC Enclosures are corrosion resistant, watertight PVC enclosures featuring simple screw down covers. Each enclosure is assembled with a PVC gasket and a screwdown lift-off cover and 4 captive brass cover screws.





APPLICATION

- Designed for general electrical; electronic applications; and any application that has associated environmental concerns
- Thermoplastic PVC junction enclosure designed for general purpose and industrial applications; including outdoor landscaping; agricultural; marinas; car washes; and residential.
- Well-suited for extremely wet applications and corrosive environments both indoor and outdoor
- Small footprint and extra deep features allow use in tight or dense spaces

FEATURES

- Corrosion resistant PVC material
- Memory retaining seamless PVC gasket
- Threaded inserts and captive brass cover screws
- Corrosion resistant PVC material
- Integral mounting feet available on some models

General Information

Color	Gray
Cover Type	Opaque
Mounting Type	Wall Mount
Material	PVC
Back Panel Screw Size	
Cover Screw Size	#8-32
Cover Screw Recommended Torque	16-20 in-lbs
Cover Screw Material	Brass
Mounting Foot Screw Size	10-16 Hi-Lo
Installation Mounting Torque	30 in-lbs Max
Metal Inserts	Brass
Gasket Material	PVC Seamless
Country of Origin	USA

DIMENSIONS

Height (in)	6.85
Width (in)	6.85
Depth (in)	4.57
Height (mm)	173.99
Width (mm)	173.99
Depth (mm)	116.078
Usable Depth (in)	4.03
Usable Depth (mm)	102
Weight (lbs)	2.12

STANDARDS

NEMA 10250; UL 50; UL 50e; UL508A	UL Listed File #E190960
CSA Std. C22.2	File 207025
Type	1; 2; 3; 4; 4X; 12; 13
Temperature Range °F	-4°F to +140°F
Temperature Range °C	-20°C to +60°C
Flammability Rating	UL94-V0
Outdoor Exposure UL746c	(f1) Rated