Enclosures PushButton Series

Polycarbonate Enclosure 4 x 3 x 2 Inches Push Button Series 1 Hole 22 mm with Yellow Lift Off Cover and Black Base


Catalog Number	YW-CFPC1PB22
UPC	785928575150

DESCRIPTION



4H x 3W x 2D Inches Push Button Series Yellow Fiberglass Enclosure is an in-line enclosures designed to be a true push button station and houses pushbuttons, switches and pilot lights in 22mm configurations. Designed for general electrical and electronic applications or any application that has associated environmental concerns. Features a black base with a yellow lift off cover.

APPLICATION



- For use in many MRO and OEM applications
- Slim design allows easy installation of pushbuttons and switches in machine control applications with tight or dense space requirements
- Used in compact or portable control systems or for use as an Operator Interface Enclosures in both indoor and outdoor environments
- These unique in-line enclosures house pushbuttons; switches and pilot lights in both 30mm and 22mm configurations

- Used indoors or outdoors
- Yellow cover complies with need for E-STOP applications.

FEATURES

- Memory retaining continuous polyurethane gasket
- Captive polymer cover screws
- Corrosion resistant polycarbonate
- Submersible; non corrosive; environmental design
- High Impact Resistance
- High visibility safety yellow cover

General Information

Color	Yellow
Cover Type	Push Button
Mounting Type	Wall Mount
Material	Polycarbonate
Cover Screw Size	Custom
Cover Screw Recommended Torque	16-20 in-lbs
Cover Screw Material	Polycarbonate
Installation Mounting Torque	25-30 in-lbs Max
Metal Inserts	None
Gasket Material	Poured In Place (PIP) Polyurethane Seamless
Country of Origin	USA

DIMENSIONS

Height (in)	4
Width (in)	3
Depth (in)	2
Height (mm)	101.6
Width (mm)	76.2
Depth (mm)	50.8
Usable Depth (in)	2.51
Usable Depth (mm)	64
Weight (lbs)	1

STANDARDS

NEMA 10250; UL 50; UL 50e; UL508A	cULus Listed File #E319779
CSA Std. C22.2	cULus Listed File #E319779
Type	1; 3R; 4; 4X; 6P; 12
IEC 60529; UL Listed #E362920	IP66; IP68
Temperature Range °F	-40°F to +248°F
Temperature Range °C	-40°C to +120°C
Flammability Rating	UL94-5VA
Outdoor Exposure UL746c	(f1) Rated
CE	Certified