Enclosures PushButton Series

# Polycarbonate Enclosure 4 x 3 x 2 Inches Push Button Series 1 Hole 30 mm with Yellow Lift Off Cover and Black Base


| | |
|---|---|
| **Catalog Number** | YW-CFPC1PB |
| **UPC** | 785928575136 |

## DESCRIPTION



4H x 3W x 2D Inches Push Button Series Yellow Fiberglass Enclosure is an in-line enclosures designed to be a true push button station and houses pushbuttons, switches and pilot lights in 30mm configurations. Designed for general electrical and electronic applications or any application that has associated environmental concerns. Features a black base with a yellow lift off cover.

## APPLICATION



- For use in many MRO and OEM applications
- Slim design allows easy installation of pushbuttons and switches in machine control applications with tight or dense space requirements
- Used in compact or portable control systems or for use as an Operator Interface Enclosures in both indoor and outdoor environments
- These unique in-line enclosures house pushbuttons; switches and pilot lights in both 30mm and 22mm configurations

- Used indoors or outdoors
- Yellow cover complies with need for E-STOP applications.

## FEATURES

- Memory retaining continuous polyurethane gasket
- Captive polymer cover screws
- Corrosion resistant polycarbonate
- Submersible; non corrosive; environmental design
- High Impact Resistance
- High visibility safety yellow cover

## General Information

| | |
|---|---|
| Color | Yellow |
| Cover Type | Push Button |
| Mounting Type | Wall Mount |
| Material | Polycarbonate |
| Cover Screw Size | Custom |
| Cover Screw Recommended Torque | 16-20 in-lbs |
| Cover Screw Material | Polycarbonate |
| Installation Mounting Torque | 25-30 in-lbs Max |
| Metal Inserts | None |
| Gasket Material | Poured In Place (PIP) Polyurethane Seamless |
| Country of Origin | USA |

## DIMENSIONS

| | |
|---|---|
| Height (in) | 4 |
| Width (in) | 3 |
| Depth (in) | 2 |
| Height (mm) | 101.6 |
| Width (mm) | 76.2 |
| Depth (mm) | 50.8 |
| Usable Depth (in) | 2.51 |
| Usable Depth (mm) | 64 |
| Weight (lbs) | 1 |

## STANDARDS

| | |
|---|---|
| NEMA 10250; UL 50; UL 50e; UL508A | cULus Listed File #E319779 |
| CSA Std. C22.2 | cULus Listed File #E319779 |
| Type | 1; 3R; 4; 4X; 6P; 12 |
| IEC 60529; UL Listed #E362920 | IP66; IP68 |
| Temperature Range °F | -40°F to +248°F |
| Temperature Range °C | -40°C to +120°C |
| Flammability Rating | UL94-5VA |
| Outdoor Exposure UL746c | (f1) Rated |
| CE | Certified |