



Accessories Fittings

PVC Coated STG Rigid Conduit Knockout Hub with Ground 1 Inch



Catalog Number **RESTPRSTG3**

UPC

785928566004

DESCRIPTION

1 Inch PVC Coated STG Rigid Conduit Knockout Hub with Ground are used for connections using rigid PVC coated conduit.



APPLICATION

- •Used with Rigid and IMC conduit to terminate of electrical circuits through wall of an enclosure
- For use indoors or outdoors with rigid conduit and IMC
- Ideal for pharmaceutical; chemical and food processing; pulp/paper; nuclear; solar and commercial construction applications

FEATURES

- Tapered female threads for rigid/IMC conduit; NPSM male threads
- Easy installation and smooth pulling service for labor savings
- Multiple certifications provide users peace of mind



Accessories

General Information

Color Gray

Material PVC Coated Rigid

Country of Origin USA

DIMENSIONS

| Dimension A (Inches) | 1.7 |
|----------------------|-----|
| Dimension B (Inches) | 2.5 |
| Dimension C (Inches) | 1.0 |
| Max Wall Thickness | 0.3 |
| Nominal Weight (lbs) | 0.4 |

STANDARDS

| NEC/CEC | Class II, Division 1 & 2 |
|---------|---------------------------|
| NEC/CEC | Class I, Division 2 |
| NEC/CEC | Class III, Division 1 & 2 |
| UL 514B | UL Listed File #E200413 |