POLYSTAR® BLACK SERIES



THE MOST INNOVATIVE, DURABLE, AND RELIABLE POLYCARBONATE ENCLOSURES — NOW AVAILABLE IN BLACK!

The new Stahlin PolyStar enclosures in black provide superior environmental protection and enhance installations. Ideal for the promotion of OEM products, they can blend in with surrounding equipment or stand out and improve aesthetics.



SUPERIOR PROTECTION AGAINST



RAIN, SLEET & SNOW



SPLASHING &
HOSE DIRECTED
WATER



SUBMERSION



SUN/UV



FLAMES



APPLICATIONS

- Extremely tough and durable, PolyStar Black Series enclosures are used in both indoor and outdoor applications. They provide superior environmental protection for customer equipment.
- Ideal for the promotion of OEM products and either blend in with their surroundings or command visual attention in applications where improved aesthetics are desired.

BENEFITS

- + Appealing aesthetics and increased visibility to improve customer promotion and branding
- Versatile, innovative features including a panel management system maximizing internal space, T-slot design for side wall mounting, and octagon mounting feet allowing for unique angling and git with equipment.
- + Impact and corrosion resistant design with full polycarbonate material construction.

INNOVATIVE FEATURES

- ♣ PolyStar is now available in black color as standard in 12" x 10" x 6", 14" x 12" x 6", and 16" x 14" x 8", opaque or smoked clear cover configurations!
- Lightweight, high-impact rated polycarbonate material construction with molded-in color that will not chip or scape away.
- + Aesthetically appealing glossy finish.
- Innovative panel management and side mount capabilities allows full use of interior space to maximize component placement and design flexibility.
- + Cover options include opaque or clear with smoke tint.
- + Stainless steel latches as standard.
- + Fully non-metallic hinge does not penetrate inside enclosure.
- + One solution enclosure can be configured as a screw cover or hinged cover.
- + Thick, robust side wall construction eliminates side wall flexing.
- + Built in DIN Rail mounting embosses in the back of the enclosure.
- + Sliding T-Nut allows for infinite panel adjustment.
- Four mounting feet, cover screws, mounting caps, back panel screws, and washers included.
- + Multi-directional mounting feet allow mounting flexibility.
- + Aluminum back panel and swing-out panel mounting options.
- Custom digital printing and modifications are available upon request through our value add ModRight program. Please consult factory.

MATERIALS

INDUSTRY STANDARDS

- **+ Enclosures and Covers:** Polycarbonate with UV inhibitors
- + Latches: Stainless steel
- + cULus Listed per file #E319779
- + IEC 60529: CULus Listed per file #E362920 IP66, IP68
- + UL 50, UL 50e, UL 508A
- + Type 1, 3R, 4, 4X, 6P, 12

- **+ Gasket:** Robotically applied Foam-in-Place seamless polyurethane
- Operating Temperature Rating:
 -40°F to +248°F (-40°C to +120°C)
- UL's best rating, an "f1" per UL 746C (resin has passed tests for UV exposure and water immersion)

CATALOG NUMBERS AND DIMENSIONS

PolyStar Black Series					
Opaque Cover Catalog #	Clear Cover Catalog #	Overall H x W x D	Back Panel Part #	Swing Kit Part #	
BK-PC1210SS	BK-PC1210CCSS	12 x 10 x 6	BP1210AL	PC1210SPK	
BK-PC1412SS	BK-PC1412CCSS	14 x 12 x 6	BP1412AL	PC1412SPK	
BK-PC1614SS	BK-PC1614CCSS	16 x 14 x 8	BP1614AL	PC1614SPK	

Note: Measurements shown are in inches.

PolyStar Black Series - Replacement Accessory Kit		
Catalog #	Description	
BK-PCACCESSORYKIT This kit is for replacement parts only. Enclosures are provided with mounting feet and hardwincluded with the enclosure catalog number.		



