



# **F Series**







| _ | · ~ | -   | + 14 1 |   | ion |
|---|-----|-----|--------|---|-----|
| _ |     | 115 |        |   |     |
|   | -   | 110 |        | 4 | 011 |
|   |     |     |        |   |     |

| Material                    | SolarGuard® – Hot compression molded fiberglass reinforced polyester (thermoset)             |
|-----------------------------|--|
| Gasket                      | Poured polyurethane seamless<br>gasket provides watertight, dust-tight<br>environmental seal |
| Cover screws                | Captive stainless steel screws   |
| Stainless<br>Steel Hardware | 300 Series stainless used<br>on all external hardware  |
| Enclosure Mounting          | Mounting wells located under the cover/outside the gasket area.                              |
| Panel Mounting              | Raised bosses with brass inserts accepting<br>10-32 screws for optional panel mounting       |
| Soft Edge Design            | Rounded edges, minimal protrusions or exposed pocket areas for assembly of dust and debris   |
| Color                       | Available in standard glacier grey<br>(Pantone 428C)   |
|                             |  |

#### **F** Modifications


| <b>Custom Colors</b> | pg. 21 <b>-</b> 22 |
|----------------------|--------------------|
| Silk Screening       | pg. 21 <b>-</b> 22 |
| EMI/RFI Shielding    | pg. 21-22          |
| <b>Custom Window</b> | pg. 21 <b>-</b> 22 |
| Custom Cutouts/Holes | pg. 21-22          |


### F Industry Standards


| NEMA 250, UL Listed<br>UL50, UL50e, UL508A | File E64358<br>Type 1, 3R, 4X, 6P, 12                 |  |  |  |  |
|--|---|--|--|--|--|
| CSA Std 22.2                               | File LR069014<br>Type 1, 3R, 4X, 6P, 12               |  |  |  |  |
| IEC 60529                                  | UL File E362920<br>IP 66, IP67, IP68                  |  |  |  |  |
| UL1741                                     | File E333478  |  |  |  |  |
| Plenum Space (UL2043)<br>Compliant         | Yes   |  |  |  |  |
| Temperature Range                          | (-76°F to +274°F)<br>(-60°C to +134°C)                |  |  |  |  |
| Flammability Rating                        | UL94-5V   |  |  |  |  |
| Impact Rating                              | IK10  |  |  |  |  |
| Self Extinguishing                         | Non-haloginated,<br>non-flame propagating             |  |  |  |  |
| Chemical Resistance                        | Full chemical resistance<br>charts listed in appendix |  |  |  |  |
| NFPA No. 101 Flame Spread                  | Class A (1)   |  |  |  |  |
| Outdoor Exposure UL746C                    | (f1) Rated  |  |  |  |  |
|  |   |  |  |  |  |


#### **F** Accessories

| BACK PANELS | Aluminum        | BP_AL | pg. 174 <b>-</b> 175 |
|-------------|-----------------|-------|----------------------|
|             | Fiberglass      | BP_FG | pg. 174 <b>-</b> 175 |
|             | Stainless Steel | BP_SS | pg. 174 <b>-</b> 175 |
|             | Carbon Steel    | BP_CS | pg. 174 <b>-</b> 175 |









- NOTES:

  1. CATALOG DRAWING IS FOR REFERENCE ONLY
  2. SEE ACTUAL PART DRAWING FOR SPECIFIC DESIGN
  3. NOTE 'J" DIMENSION IS WITH 0.080" THICK BACK PANEL INSTALLED
  4. BACK PANEL IS SOLD SEPARATELY

#### **SCREW SIZES & TORQUE VALUES**

| PRODUCT SIZES | BACK PANEL<br>SCREW SIZE | BACK PANEL<br>RECOMMENDED TORQUE | COVER<br>SCREW SIZE   | COVER SCREW RECOMMENDED TORQUE | RECOMMENDED MOUNTING FLANGE TORQUE |  |  |
|---------------|--------------------------|----------------------------------|-----------------------|--------------------------------|------------------------------------|--|--|
| All Sizes     | N/A                      | N/A                              | #10 <b>-</b> 24 x 3/4 | 20 - 24 in-lbs                 | 45 in-lbs max                      |  |  |

## **F Series**

| CATALOG<br>NUMBER | OVERALL<br>H X W X D                   | INSIDE<br>A X B X C                    | MOUNTING<br>E X F          | J            | К             | L             | М             | N            | SHIP<br>WEIGHT | PANEL<br>NUMBER |
|-------------------|--|--|----------------------------|--------------|---------------|---------------|---------------|--------------|----------------|-----------------|
| F763              | 7.63 x 6.63 x 3.19<br>(194 x 168 x 81) | 6.90 x 5.90 x 2.88<br>(175 x 150 x 73) | 5.37 x 5.63<br>(137 x 143) | 2.48<br>(63) | 5.37<br>(137) | 4.25<br>(108) | 4.52<br>(115) | 4.9<br>(124) | 2.5 lbs.       | BP76*           |
| F963              | 9.87 x 6.63 x 3.19<br>(251 x 168 x 81) | 9.15 x 5.90 x 2.88<br>(232 x 150 x 73) | 7.62 x 5.63<br>(194 x 143) | 2.48<br>(63) | 7.62<br>(194) | 4.25<br>(108) | 6.77<br>(172) | 4.9<br>(124) | 2.6 lbs.       | BP96*           |

All measures are in inches, items in parentheses are in millimeters.



\*Panel sold separately