



DETAIL A
 WINDOW MATERIAL: S.A.R. ACRYLIC, 1/4" THICK
 ABRASE INSIDE COVER SURFACE PRIOR TO BONDING
 WINDOW BONDED USING MA-320
 WINDOW SURFACE FLUSH TOLERANCE: +0.020 / -0.030
 0.010 MAX. EXPANSION GAP BETWEEN COVER CUTOUT & WINDOW

THIS DRAWING IS THE SOLE AND EXCLUSIVE PROPERTY OF STAHLIN AND CO. NO PART OF THIS DRAWING MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT THE EXPRESS WRITTEN PERMISSION OF STAHLIN INDUSTRIES. ALL RIGHTS RESERVED UNDER THIS COPYRIGHT AND DESIGN PATENT PROTECTION.

SPECIAL REQUIREMENTS

NEMA 250 TYPE 1, 3, 3R, 4X, 12, 13		STANDARD PIN:	JW100806HPL	ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED	TOLERANCES UNLESS SPECIFIED	XX ±0.03	XXX ±0.010
REF: 4029 (REV)		COLOR:	GLACIER GRAY (IMPRES)	CUSTOMER DWG:			
COLOR STANDS: PANTONE 351C		MATERIAL: FIBERGLASS REINFORCED POLYESTER (FRP)		STAHLIN A DIVISION OF ROBROY INDUSTRIES 500 Maple Street Belding, Michigan 48809 Phone: 616-794-2700 Fax: 616-749-3373			
REVISION HISTORY		DATE	ENG	SCALE:	DESCRIPTION	PART NUMBER	DWG
REV	DESCRIPTION			2	DO NOT SCALE	STANDARD ENCLOSURE	JW100806HPL
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-