




THIS DRAWING IS THE SOLE AND EXCLUSIVE
PROPERTY OF ROBROY ENCLOSURES.
NO PART OF THIS DRAWING MAY BE
REPRODUCED, DISTRIBUTED, OR PUBLICALLY
DISPLAYED IN ANY FORM OR BY ANY MEANS
WITHOUT THE EXPRESS WRITTEN
PERMISSION OF ROBROY ENCLOSURES.
ALL RIGHTS RESERVED
UNDER THE COPYRIGHT LAWS.
COPYRIGHT © 2023 ROBROY ENCLOSURES

SPECIAL REQUIREMENTS

- ASSEMBLY:**
1. LATCHES NOT REQUIRED
 2. (1) ACCESSORY KIT (WPPCACCKIT) SHALL BE PACKAGED LOOSELY INSIDE ENCLOSURE
 3. (1) STYROFOAM SHEET SHALL BE PLACED ON TOP OF COVER INSIDE CARTON

NEMA 250: TYPE 1, 3R, 4, 4X, 6P, 12 IEC 60529: IP66, IP68 COLOR: N/A COLOR STANDARD: PANTONE 7541 C				STANDARD P/N: PC1614HW		ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED		TOLERANCES UNLESS SPECIFIED		.XX ± 0.03 .XXX ± 0.010	
MATERIAL: POLYCARBONATE						 STAHLIN A ROBROY ENCLOSURES™ BRAND		Robroy Enclosures 500 Maple Street Belding, Michigan 48809 Phone: 616-794-0700 Fax: 616-749-3378			
REVISION HISTORY											
REV	DESCRIPTION			DATE	ENG	DRAWN BY AA	DATE 11/22/23	CUSTOMER		DWG PC1614HW	
-	-			-	-	SCALE		DESCRIPTION		PART NUMBER	
-	-			-	-	DO NOT SCALE		STANDARD ENCLOSURE		FEPC1614HW	
-	-			-	-						
-	-			-	-						
-	-			-	-						